



Kuhner shaker

www.kuhner.com

The world's most reliable shaking machines

Kuhner shaker • since 1949

Our motto: To build the world's most reliable shakers

Kuhner AG is the leading developer and manufacturer of shaking machines for the international market. This family business, founded in 1949 by Mr Adolf Kühner, is now lead by his son Markus Kühner.

From bench top shakers to large scale industrial shakers, Kuhner offers machines of the highest quality. The «Kuhner shakers» name stands for functionality, reliability and durability. Kuhner designs and builds many components in-house and guarantees them for 5 years.

All processes are SN EN ISO 9001 certified. Kuhner fosters close contact with research and development departments in notable universities and companies. We constantly investigate new developments looking for opportunities to further optimise the design and performance of our shakers.

Kuhner offers a personal service for customers, including product information, support and on-site visits.



Kuhner shaker

From bench top shakers to large industrial shakers, Kuhner AG manufactures high quality machines for customers around the world.
www.kuhner.com

4	Overview	22	Lab-Shakers LS-X & ES-X	30	Accessories
6	Features	24	Rack System	38	Add-ons
	Incubator Shakers				
12	LT-X / LT-XC	25	Pilot-Shakers RC2-X & SR200-X		
14	ISF1-X / ISF1-XC				
16	ISF4-X / ISF4-XC	26	OrbShakers SB50-X & SB200-X		
18	Shaker Laboratory				
20	Options	28	Custom-made		

Shaking solutions for research and production

5
YEAR
5 Year Warranty

Incubator Shakers

Available with controlled CO₂ & humidity



LT-X (Lab-Therm)



ISF1-X (Climo-Shaker)



ISF4-X (Climo-Shaker)

Pilot-Shakers

Orbital shaking



RC2-X

SR200-X

OrbShakers

Easy scale-up



SB50-X OrbShake

SB200-X OrbShake

Lab-Shakers

Continuous, maintenance-free operation



LS-X

ES-X

Rack System

Adaptable and Extendable



SBM/SS-X



Direct drive

- Low energy consumption
- Smooth running and quiet operation
- Option of 3 direct drives:
Standard, high speed, high power



Changeable diameter

Diameter can be adjusted by the user at any time

- Three standard shaking diameters:
12.5 mm, 25 mm and 50 mm
- Other shaking diameters are also possible:
e.g. 70 mm for liquids with high viscosity



Parallelogram

The parallelogram ensures identical shaking movement anywhere on the tray, regardless of load distribution. The double steel springs will last a lifetime.



Only Kuhner can provide multiple shaking diameters in a single shaker.



Foamed insulation

The key to our precise KuhnerControl is the unique insulation process with CFC-free foam.


Foaming is done by hand to ensure:

- Precise control of process parameters
- No condensation between insulation and casing
- Reduced energy consumption



Temperature control

Homogeneous temperature distribution across the entire shaking tray of a Kuhner incubator shaker ensures reproducible cultivation results. Precise temperature control with low energy consumption is guaranteed.



CO₂ control

Reliable control of CO₂ is essential when working with mammalian or plant cell cultures and also algae. A CO₂ controlled atmosphere inside the shaker incubator allows exact pH adjustment of the culture medium. Kuhner was the first company to manufacture and supply shakers with CO₂ control, so you can rely on our many years of experience.



Humidity control

Controlled humidity is an important factor when working with microtiter plates, or when cultivating in flasks for long periods (e.g. cell cultures), as humidity can significantly reduce evaporation. Heated windows and door frames prevent condensation.



Control

Kuhner shakers are characterised by their user friendly controls. Every process parameter has its own controller and navigation is extremely simple.






For convenient supervision of the shaker

Kuhner Insight Software

Kuhner Insight is our user-friendly software for data recording, calibration, programming and controlling. Simultaneous recording of process parameters for up to 8 shakers is possible.

Interface

Our wide range of interfaces keep you well connected.



Order number	Interface	Order number	Interface
SMX856000	Kuhner Insight Software	SMX856501	NET-60 - Modbus/TCP
SMX856011	Interface: CAN-USB	SMX856502	NET-60 - Modbus/RTU
SMX856020	Interface: CAN-Ethernet	SMX856503	NET-60 - DeviceNet
SMX856030	External machine interface: EMI-60	SMX856504	NET-60 - PROFINET I/O
		SMX856505	NET-60 - PROFIBUS DP-V1
		SMX856506	NET-60 - EtherNet/IP

LT-X / LT-XC

- Used in biotechnology and pharmaceutical industries
- XC incubator shakers are optimised for cell cultivation



- Fits in any laboratory
- Accepts flasks up to 6 litres
- Two units can be stacked without the need for special tools or stacking kits



CO₂ control option available: essential for mammalian, plant cell cultures and algae

Heating and cooling

Controlled humidity option: essential for cultivation in microtiter plates or when cultivating in flasks for long periods

Heated window and door frame with controlled humidity option


User-friendly operation: each parameter has its own control

Retrofitting possible

Technical data

• Overview	SMX1700 / SMX1700C*	SMX1701 / SMX1701C*	SMX1703 / SMX1703C*
Cooling	no	yes	yes
Humidity control	no	no	yes
Temperature minimum	ambient + 10 °C	ambient - 15 °C (- 10 °C)*	ambient - 15 °C (- 10 °C)*
Temperature maximum	80 °C (60 °C)*	80 °C (60 °C)*	80 °C (60 °C)*
Humidity maximum	-	-	85% r.h.
Power consumption	< 800W	< 950W	< 1300W
• Machine			
Gas volume	260 litre		
Weight (with cooling)	170 kg		
Illumination	LED		
Ambient temperature	10 °C up to 35 °C		
• Display / Interface			
Operating menu in	de, fr, it, en, es		
Interface, standard	CAN-Bus		
Interface, optional	USB, Ethernet, digital, analogue		
• Temperature			
Setting, digital	0.1 °C		
Accuracy, absolute	± 0.30 °C (37 °C)		
(across the tray)	± 0.25 °C (37 °C)*		
Principle of sensor	PT-100		
Power of heating	500W		
Power of cooling	90... 155W		
Air circulation	160 m ³ /h		
• Shaking unit			
Tray, size	EX (500 × 420 mm)		
Loading, maximum	25 kg		
Setting, digital	1 rpm		
Accuracy, absolute	± 0.1 rpm		
Timer	1s... 999h		
Acceleration	controlled		
Active brake	adjustable		
Stop on position	adjustable		
• Shaking motion			
	Speed		
orbital, Ø 12.5mm *	20... 500 rpm		
orbital, Ø 25.0mm *	20... 400 rpm		
orbital, Ø 50.0mm *	20... 300 rpm		
linear 12.5mm *	20... 400 rpm		
linear 25.0mm *	20... 300 rpm		
linear 50.0mm *	20... 200 rpm		
* can be changed / other diameters on request			
• Humidity (SMX1703)			
Max. at 25... 55 °C	85% r.h.		
Setting, digital	1% r.h.		
Accuracy, absolute	± 2% r.h.		
Principle of sensor	capacitive		
Water refill	automatic		
Water heater	180W		
Door heater	90W		
• CO₂ (SMX1034)			
Principle of sensor	Infrared, NDIR		
Measuring range	0... 20% CO ₂		
Setting, digital	0.1%		
Accuracy, absolute	± 0.40% at 5% CO ₂		
(including non-linearity, calibration uncertainty and repeatability)			
Temperature range	5... 60 °C		
CO ₂ -supply	max. 2 bar overpressure		
• Mains connection			
SMX1021	220-240 V / 50-60 Hz		
SMX1022	190-210 V / 50-60 Hz		
SMX1023	110-120 V / 50-60 Hz		
SMX1024	95-105 V / 50-60 Hz		
• Further Options			
SMX1771	UV lamp		
SMX1773	Black window		
SMX1742	Unit for photosynthesis (LED)		
SMX1712A	TabCom		
SMX1772	Shelf		
Dual table available on request			
* optimised incubator shaker for cell culture			
+ CO ₂ control (SMX1034) included as standard			
+ Temperature max: 60 °C			
+ Improved temperature accuracy: ± 0.25 °C (37 °C)			

Dimensions (mm)



ISF1-X / ISF1-XC

XC incubator shakers are optimised for cell cultivation

-  CO₂ control option available: essential for mammalian, plant cell cultures and algae
-  Heating and cooling
-  Controlled humidity option: essential for cultivation in microtiter plates or when cultivating in flasks for long periods
-  Heated window and door frame with controlled humidity option
-  User-friendly operation: each parameter has its own control
-  Retrofitting possible

stack up to 3 shakers

Easy to stack without the need for special tools or stacking kits




Upward opening door

Technical data

	SMX1500 / SMX1500C*	SMX1501 / SMX1501C*	SMX1503 / SMX1503C*
• Overview			
Cooling	no	yes	yes
Humidity control	no	no	yes
Temperature minimum	ambient + 10 °C	ambient - 15 °C (- 10 °C)*	ambient - 15 °C (- 10 °C)*
Temperature maximum	80 °C (60 °C)*	80 °C (60 °C)*	80 °C (60 °C)*
Humidity maximum	-	-	85% r.h.
Power consumption	< 1300W	< 1500W	< 2000W
• Machine			
Gas volume	395 litre		
Weight (with cooling)	210 kg		
Illumination	LED		
Ambient temperature	10 °C up to 35 °C		
• Humidity			(SMX1503)
Max. at 25...55 °C			85% r.h.
Setting, digital			1% r.h.
Accuracy, absolute			± 2% r.h.
Principle of sensor			capacitive
Water refill			automatic
Water heater			300W
Door heater			100W
• Display / Interface			
Operation menu in	de, fr, it, en, es		
Interface, standard	CAN-Bus		
Interface, optional	USB, Ethernet, digital, analogue		
• Temperature			
Setting, digital	0.1 °C		
Accuracy, absolute	± 0.30 °C (37 °C)		
(across the tray)	± 0.25 °C (37 °C)*		
Principle of sensor	PT-100		
Power of heating	1000W		
Power of cooling	155...270W		
Air circulation	300m ³ /h		
• Shaking unit			
Tray, size	F (800 x 420 mm)		
Loading, maximum	25kg		
Setting, digital	1 rpm		
Accuracy, absolute	± 0.1 rpm		
Timer	1s...999h		
Acceleration	controlled		
Active brake	adjustable		
Stop on position	adjustable		
• Shaking motion		Speed	
orbital, Ø 12.5 mm *	20...500 rpm		
orbital, Ø 50.0 mm *	20...400 rpm		
orbital, Ø 50.0 mm **	20...300 rpm		
linear, 12.5 mm *	20...400 rpm		
linear, 25.0 mm *	20...300 rpm		
linear, 50.0 mm *	20...200 rpm		
* can be changed / other diameters on request			
• Mains connection			
SMX1021	220-240 V / 50-60 Hz		
SMX1022	190-210 V / 50-60 Hz		
SMX1023	110-120 V / 50-60 Hz		
SMX1024	95-105 V / 50-60 Hz		
• Further Options			
SMX1033	Pull-out table		
SM1542	Unit for photosynthesis (LED)		
SMX1571	UV lamp		
SMX1573	Black window		
SMX1512A	Tab-Com for standard shaking unit		
SMX1512B	Tab-Com for unit with pull-out table		
SMX1572	Shelf		
Dual table available on request			
• Optimised incubator shaker for cell culture			
+ CO ₂ control (SMX1034) included as standard			
+ Temperature max: 60 °C			
+ Improved temperature accuracy: ± 0.25 °C (37 °C)			

Dimensions (mm)



ISF4-X / ISF4-XC

XC incubator shakers are optimised for cell cultivation

-  CO₂ control option available: essential for mammalian, plant cell cultures and algae
-  Heating and cooling
-  Controlled humidity option: essential for cultivation in microtiter plates or when cultivating in flasks for long periods
-  Heated window and door frame with controlled humidity option
-  User-friendly operation: each shaking unit and parameter has its own control
-  Retrofitting possible

Four shakers – one footprint


- 4 or even 5 independent, height adjustable shaking units
- Clear view of incubator's contents



Technical data

	SMX1600 / SMX1600C*	SMX1601 / SMX1601C*	SMX1603 / SMX1603C*
• Overview			
Cooling	no	yes	yes
Humidity control	no	no	yes
Temperature minimum	ambient + 10 °C	ambient – 15 °C (- 10 °C)*	ambient – 15 °C (- 10 °C)*
Temperature maximum	80 °C (60 °C)*	80 °C (60 °C)*	80 °C (60 °C)*
Humidity maximum	–	–	85% r.h.
Power consumption	< 1700W	< 2000W	< 2600W
• Machine			
Gas volume	1272 litre		
Weight (without SF-X)	520 kg		
Illumination	2 fl lamps		
Ambient temperature	10 °C up to 35 °C		
• Humidity			(SMX1603)
Max. at 25...55 °C			85% r.h.
Setting, digital			1% r.h.
Accuracy, absolute			± 2% r.h.
Principle of sensor			capacitive
Water refill			automatic
Water heater			300W
Door heater			220W
• Display / Interface			
Operating menu in	de, en, fr, it, es		
Interface, standard	CAN-Bus		
Interface, optional	USB, Ethernet, digital, analogue		
• Temperature			
Setting, digital	0.1 °C		
Accuracy, absolute (across the tray)	± 0.30 °C (± 0.7 °C)		
Principle of sensor	PT-100		
Power of heating	1000W		
Power of cooling	250...420W		
Air circulation	700m ³ /h		
• Shaking unit SF-X		(SMX1610)	
Tray, size	F (800 x 420 mm)		
Loading, maximum	25 kg		
Setting, digital	1 rpm		
Accuracy, absolute	± 0.1 rpm		
Timer	1s...999h		
Acceleration	controlled		
Active brake	adjustable		
Stop on position	adjustable		
• Shaking motion		Speed	
orbital, Ø 12.5 mm *		20...500 rpm	
orbital, Ø 25.0 mm *		20...400 rpm	
orbital, Ø 50.0 mm *		20...300 rpm	
linear 12.5 mm *		20...400 rpm	
linear 25.0 mm *		20...300 rpm	
linear 50.0 mm *		20...200 rpm	
* can be changed / other diameters on request			
• Mains connection			
SMX1021			220–240 V / 50–60 Hz
SMX1022			190–210 V / 50–60 Hz
• Further Options			
SMX1033			Pull-out table
SMX1671G			Integrated UV lamp
SMX1673			Black window (2x)
SM1642			Unit for photosynthesis (LED)
SMX1612A			TabCom for standard shaking unit
SMX1612B			TabCom for unit with pull-out table
SMX1672			Shelf
Shelf available on request			
• Optimised incubator shaker for cell culture			
+ CO ₂ control (SMX1034) included as standard			
+ Temperature max: 60 °C			

Dimensions (mm)





Knowledge transfer

Shaker Laboratory

Kuhner AG offers advice on cultivations in shaken bioreactors. Our in-house laboratory uses a number of online-measuring methods and computer based models to support our customers.

Collaboration with universities, especially with academic partners Prof. Büchs (AVT, RWTH Aachen, Germany) and Prof. Wurm (LBTC, EPFL Lausanne, Switzerland), can also provide answers to complex questions.

This consultation service is confidential of course and free of charge for Kuhner customers. Kuhner is also part of the Forum Shaking Technology, a collection of partner companies involved in different areas of the laboratory & biotechnology industry. Its website is a helpful resource for users of shaken bioreactors, providing support, information and a publication data base focusing on shaken bioreactors. www.shakingtechnology.com

Furthermore, Kuhner carries out seminars which address questions about cultivation conditions and offer suggestions for optimising the operation of your shaken bioreactors (shake flasks, microtiter plates, tubespins etc.).

A scientific poster gallery on our website completes our support service. Posters can be enlarged and downloaded. Take a look. www.kuhner.com

Seminars and Trainings

New Seminar and Training Center near Barcelona



Options



UV lamp

The chamber of an incubator shaker can be sterilized with an integrated UV lamp. The UV lamp has a clearly labelled external switch.



Black window

Available for light sensitive medium or organisms. Any Kuhner incubator shaker can be delivered with blackened windows to prevent unwanted daylight or UV radiation inside the incubator.



Pull-out table

With a pull-out table loading and unloading trays is much easier.



Dual table

The dual table is an easy and economical way of doubling the shaking capacity. It consists of two levels. Each level will accept an E, EX or F size tray. However, the shaking speed is limited to a maximum of 200 rpm.



Illumination unit for photosynthesis (LED)

The ceiling of any Kuhner incubator shaker can be fitted with LED modules for the cultivation of phototrophic organisms. The control module allows full programming of night/day cycles and variable light intensity.

- Order this unit together with cooling.



Standard shaking unit

Pull-out table

TabCom

The TabCom option from Kuhner consists of a cable for power and data with the connection port integrated in the shaking table (CAN-Bus & 24 V power supply).

A cable guide prevents the cable breaking and ensures secure data recording. Online measuring technologies offered by Kuhner that use TabCom include BPM-60 (pH, dissolved oxygen) and RAMOS (OTR, CTR). The flexibility of TabCom means other measurement systems can be easily integrated.



Shelf

The incubator shakers as well as the Rack System can be fitted with a shelf allowing cultivation in petri dishes. The shelf is fitted above the shaking table.



IQ/OQ Documentations

IQ-OQ (Installation Qualification and Operation Qualification) is an equipment qualification required for GMP procedures.

Documentation is available from Kuhner and Qualification services can also be provided at the customer's premises.

- Available for each shaker

Lab-Shakers

LS-X

Sturdy bench top shaker

- Accepts loads up to 25 kg
- Large display and touch pad control
- Ideal base for customised trays and holders



ES-X

For use in incubators with humidity

- Separate control unit
- Ideal for cell culture applications
- Special version available for robotic systems
- Minimal heat transfer and low energy consumption



Technical data

Overview	LS-X (SMX1200)	ES-X (SMX1300)
Weight	58 kg	60 kg
Operating menu in	de, fr, it, en, es	de, fr, it, en, es
Interface, standard	CAN-Bus	CAN-Bus
Interface, optional	USB, Ethernet, digital, analogue	USB, Ethernet, digital, analogue
Ambient temperature	0 °C up to 60 °C	-20 °C up to 80 °C
Control unit	0 °C up to 60 °C	0 °C up to 60 °C
Consumption, maximum	65W (130W with high torque drive SMX101)	65W (130W with high torque drive SMX101)
Consumption, typical	25W	25W

(Details for both Lab-Shakers)


Shaking unit	
1 x Tray, size	E (420 x 420 mm) or EX (500 x 420 mm) or F (800 x 420 mm)
Loading, maximum	25 kg
Setting, digital	1 rpm
Accuracy, absolute	± 0.1 rpm
Timer	1s ... 999h
Acceleration	controlled
Active brake	adjustable
Stop on position	adjustable

Shaking motion		Speed	
orbital, Ø 12.5 mm *		20 ... 500 rpm	
orbital, Ø 25.0 mm *		20 ... 400 rpm	
orbital, Ø 50.0 mm *		20 ... 300 rpm	
linear, 12.5 mm *		20 ... 400 rpm	
linear, 25.0 mm *		20 ... 300 rpm	
linear, 50.0 mm *		20 ... 200 rpm	


* can be changed/other diameters as request

Mains connection	
SMX1021	220-240 V / 50-60 Hz
SMX1022	190-210 V / 50-60 Hz
SMX1023	110-120 V / 50-60 Hz
SMX1024	95-105 V / 50-60 Hz

Dimensions (mm)



Dimensions (mm)



Rack System

Extendable Rack System

SBM/SS-X

- Ideal for temperature controlled rooms, laboratories and corridors
- Each shaking unit has its own direct drive
- Size and configuration can be altered at any given time



• Technical data		SBM: SMX1900 / SEM: SMX1901
Weight SBM		54 kg
Consumption, maximum		240 W (4 machines, max. acceleration)
Consumption, maximum		480 W (4 machines with high torque drive)
Consumption, typical		50 W (4 machines)
Ambient temperature		0 °C up to 60 °C

• Display / Interface	
Operating menu in	de, fr, en, it, es
Interface, standard	CAN-Bus
Interface, optional	USB, Ethernet, digital, analogue

• Shaking unit SS-X		SMX1910
Weight SS-X		60 kg
Tray, size		F (800 x 420 mm)
Loading, maximum		25 kg
Setting, digital		1 rpm
Accuracy, absolute		± 0.1 rpm
Timer		1s ... 999 h
Acceleration		controlled
Active brake		adjustable
Stop on position		adjustable
• Shaking motion		
orbital, Ø 12.5 mm *	20 ... 500 rpm	
orbital, Ø 25.0 mm *	20 ... 400 rpm	
orbital, Ø 50.0 mm *	20 ... 300 rpm	
linear 12.5 mm *	20 ... 400 rpm	
linear 25.0 mm *	20 ... 300 rpm	
linear 50.0 mm *	20 ... 200 rpm	

* can be changed / other diameters on request

• Mains connection	
SMX1021	220–240 V / 50–60 Hz
SMX1022	190–210 V / 50–60 Hz
SMX1023	110–120 V / 50–60 Hz
SMX1024	95–105 V / 50–60 Hz

Dimensions (mm)



Pilot-Shakers

- Ideal for climate controlled rooms
- Orbital shaking with maximum speed of 400 rpm
- Standard orbital shaking diameter of 50 mm

RC2-X

Two large C-size trays (800 x 660 mm)



• Technical data		SMX2120
Dimensions W x D x H		950 x 1013 x 1023
Speed		20–300 rpm
		up to 400 rpm on request
Diameter		50 mm (orbital motion)
		other diameters on request
Weight		330 kg
Accuracy, absolute		0.1 rpm
Setting, digital		1 rpm
Active brake		adjustable
Interface		CAN-Bus, RS232
Loading, maximum		100 kg
Tray size		2x C-tray (800 x 660 mm)

• Kuhner Insight Software	
Monitoring	shaking speed

• Mains connection	
SMX1021	220–240 V / 50–60 Hz
SMX1022	190–210 V / 50–60 Hz
SMX1023	110–120 V / 50–60 Hz
SMX1024	95–105 V / 50–60 Hz

SR200-X

For heavy loads and use of various vessels



• Technical data		SMX2102
Dimensions W x D x H		950 x 1013 x 892
Speed		20–300 rpm
		up to 400 rpm on request
Diameter		50 mm (orbital motion)
		other diameters on request
Weight		340 kg
Accuracy, absolute		0.1 rpm
Setting, digital		1 rpm
Active brake		adjustable
Interface		CAN-Bus, RS232
Loading, maximum		100 kg

• Kuhner Insight Software	
Monitoring	shaking speed

• Mains connection	
SMX1021	220–240 V / 50–60 Hz
SMX1022	190–210 V / 50–60 Hz
SMX1023	110–120 V / 50–60 Hz
SMX1024	95–105 V / 50–60 Hz

OrbShakers

Orbital shaken bioreactors for single-use bags

- For use in research, process development or production
- Cultivation of human, mammalian and plant cells
- Online measurement of pH and DO
- Single-use bag: requires no additional mixing device, enables quick set up times and eliminates elaborate cleaning and sterilising procedures
- Heating or cooling
- Fast turnaround
- Control unit with touchscreen monitor, software, gas mixing device & pumps

SB50-X OrbShake



SB200-X OrbShake




Technical data


• Overview		SB50-X (SMX7500)	SB200-X (SMX7100)
Shaker speed		max. 150 rpm	max. 80 rpm
Shaker diameter		50 mm (orbital motion)	50 mm (orbital motion)
Weight		approx. 340 kg without liquid	approx. 400 kg without liquid
Accuracy, absolute		0.1 rpm	0.1 rpm
Setting, digital		1 rpm	1 rpm
Active brake		adjustable	adjustable
Interface		CAN-Bus, RS232	CAN-Bus, RS232
Temperature		up to 50 °C	up to 50 °C
Cooling		cooling coils are incorporated for connection to an external cooling system (pressure < 0.2 bar)	cooling coils are incorporated for connection to an external cooling system (pressure < 0.2 bar)
Single-use bag		SMX75001	SMX71001
Mains connection			
SMX1021		220–240 V / 50–60 Hz	
SMX1023		110–120 V / 50–60 Hz	
SMX1024		95–105 V / 50–60 Hz	
Reader Box		SMX7130	
Oxygen sensor		optical measuring method	
Range		0–100%	
Accuracy		± 0.01% O ₂ at 0.21% O ₂	
		± 0.1% O ₂ at 20.9% O ₂	
Drift		< 0.015% O ₂ per day	
Temperature range		up to 50 °C	
pH sensor		optical measuring method	
Range		5.5 – 9.5	
Accuracy		± 0.05 pH at pH 7 with one point calibration	
		± 0.10 pH at pH 7 with pre calibration	
Drift		< 0.005 pH per day	
Temperature range		up to 50 °C	
Filter heater			SMX7120
Capacity		2 exhaust filters	
Temperature range		Ambient temperature up to 45 °C, monitored and controlled by Kuhner software	
Control unit			SMX7110
		with touchscreen monitor, Kuhner software, gas mixing device & pumps	

Dimensions (mm)

SB50-X OrbShake




SB200-X OrbShake



Custom-made

Tell us your requirements!

Send us a sample of the container that needs to be shaken.
We will build a suitable holder.



Custom-made accessories, an every-day occurrence for us.


High performance Swiss Technology
by Kuhner AG

Accessories

Universal system
FU-tray with various holders



Universal Trays



Order number	Description
SM3 002	Universal tray EU (420 x 420 mm)
SMX3 002	Universal tray EXU (600 x 420 mm)
SM3 003	Universal tray FU (800 x 420 mm)
SM3 004	Universal tray CU (800 x 660 mm)

EU (420 x 420 mm)

Clamps



Clamps for Erlenmeyer flasks		Number of clamps per Universal tray*			
Order number	Erlenmeyer flask size	Tray EU 420 x 420 mm	Tray EXU 500 x 420 mm	Tray FU 800 x 420 mm	Tray CU 800 x 660 mm
SM3 10025	25 ml	80	90	113	175
SM3 10050	50 ml	49	56	100	143
SM3 10100	100 ml	36	45	72	88
SM3 10125	125 ml	26	35	50	99
SM3 10150	150 ml	25	35	50	96
SM3 10200	200 ml	24	27	44	64
SM3 10250	250 ml	20	24	40	58
SM3 10300	300 ml	18	22	37	56
SM3 10500	500 ml	14	16	27	42
SM3 11000	1000 ml	9	10	16	20
SM3 11500	1500 ml	5	6	12	16
SM3 12000	2000 ml	5	5	9	12
SM3 12000F	2000 ml Fernbach	2	3	5	8
SM3 13000F	3L Thomson/ 3L Corning Fernbach	2	2	5	8
SM3 13000	3000 ml	4	5	8	11
SM3 14000	4000 ml	2	3	5	8
SM3 15000	5000 ml	2	3	4	6
SM3 16000	6000 ml	1	2	4	6

* This information on U-trays is not guaranteed due to flask size variation from different manufacturers.

Test tube holders



Order number	Tube size	Description	Number of holders per Universal tray		
			EU (420 × 420 mm)	EXU (500 × 420 mm)	FU (800 × 420 mm)
SM317016	16 mm dia. (15 ml Falcon)	RGH-16 24 tubes	5	6	9
SM317018	18 mm dia.	RGH-18 24 tubes	5	6	9
SM317020	20 mm dia.	RGH-20 18 tubes	5	6	9
SM317025	25 mm dia.	RGH-25 16 tubes	3	4	6
SM317028	28 mm dia. (50 ml Falcon)	RGH-28 16 tubes	3	4	6
SM317030	30 mm dia.	RGH-30 14 tubes	3	4	6
SM317032	32 mm dia.	RGH-32 14 tubes	3	4	6
SM317034	34 mm dia.	RGH-34 14 tubes	3	4	6

High capacity tube holders



Order number	Description	Number of holders per Universal tray		
		EU (420 × 420 mm)	EXU (500 × 420 mm)	FU (800 × 420 mm)
SMX3805	Holder for 24 × 50 ml Falcon/TPP tubes	2	3	5
SM317098	Holder for 3 × 600 ml reactors	2	3	5

Sticky strips



Order number	Description
SMX837001	1 sticky strip (385 × 85 × 3 mm)
SMX833001	Set of sticky strips for E-size tray (4 strips)
SMX834001	Set of sticky strips for EX-size tray (5 strips)
SMX835001	Set of sticky strips for F-size tray (8 strips)

Holder for deep well microtiter plates (Duetz System)




Order number	Description	Number of holders per Universal tray		
		EU (420 × 420 mm)	EXU (500 × 420 mm)	FU (800 × 420 mm)
SM318000	Single Duetz Holder	8	10	16

Special universal tray, FUM-V



Order number	Description
SMX310001	Special universal tray, FUM-V with V support (E-tange not included)
SM313000F	U-3000F clamp for Fernbach flasks: 1 × 5L Thomson flask or 1 × 3L Corning Fernbach culture flask

Trays with fixed clamps



- E-tray (420 x 420 mm)

Order number	Description	Number of clamps
SM320025	E- 25 ml	81
SM320050	E- 50 ml	50
SM320100	E- 100 ml	39
SM320125	E- 125 ml	30
SM320150	E- 150 ml	30
SM320200	E- 200 ml	20
SM320250	E- 250 ml	18
SM320300	E- 300 ml	15
SM320500	E- 500 ml	12
SM321000	E-1000 ml	9
SM321500	E-1500 ml	5
SM322000	E-2000 ml	5
SM323000	E-3000 ml	4
SM324000	E-4000 ml	2
SM325000	E-5000 ml	2
SM326000	E-6000 ml	1

- F-tray (800 x 420 mm)

Order number	Description	Number of clamps
SM330025	F- 25 ml	153
SM330050	F- 50 ml	100
SM330100	F- 100 ml	74
SM330125	F- 125 ml	60
SM330150	F- 150 ml	60
SM330200	F- 200 ml	40
SM330250	F- 250 ml	40
SM330300	F- 300 ml	30
SM330500	F- 500 ml	26
SM331000	F-1000 ml	16
SM331500	F-1500 ml	12
SM332000	F-2000 ml	9
SM332800	F-2800ml	6
SM333000	F-3000 ml	8
SM334000	F-4000 ml	5
SM335000	F-5000 ml	4
SM336000	F-6000 ml	3

- EX-tray (500 x 420 mm)

Order number	Description	Number of clamps
SMX320025	EX- 25 ml	90
SMX320050	EX- 50 ml	60
SMX320100	EX- 100 ml	42
SMX320125	EX- 125 ml	36
SMX320150	EX- 150 ml	32
SMX320200	EX- 200 ml	25
SMX320250	EX- 250 ml	21
SMX320300	EX- 300 ml	18
SMX320500	EX- 500 ml	14
SMX321000	EX-1000 ml	9
SMX321500	EX-1500 ml	8
SMX322000	EX-2000 ml	5
SMX323000	EX-3000 ml	4
SMX324000	EX-4000 ml	3
SMX325000	EX-5000 ml	3
SMX326000	EX-6000 ml	2

- C-tray (800 x 660 mm)

Order number	Description	Number of clamps
SM340025	C- 25 ml	238
SM340050	C- 50 ml	153
SM340100	C- 100 ml	116
SM340125	C- 125 ml	96
SM340150	C- 150 ml	96
SM340200	C- 200 ml	75
SM340250	C- 250 ml	65
SM340300	C- 300 ml	55
SM340500	C- 500 ml	42
SM341000	C-1000 ml	24
SM341500	C-1500 ml	18
SM342000	C-2000 ml	15
SM343000	C-3000 ml	11
SM344000	C-4000 ml	8
SM345000	C-5000 ml	6
SM346000	C-6000 ml	6

Trays for microtiter plates



- E-tray (420 x 420 mm)

Order number	Description	Number of MTP
SM3502.22	E-MT.22	12-24
SM3502.47	E-MT.47	12-48
SM3502.77	E-MT.77	12-72

- F-tray (800 x 420 mm)

Order number	Description	Number of MTP
SM3503.22	F-MT.22	24-48
SM3503.47	F-MT.47	24-96
SM3503.77	F-MT.77	24-144

- C-tray (800 x 660 mm)


Order number	Description	Number of MTP
SM3504.22	C-MT.22	35-70
SM3504.47	C-MT.47	35-140
SM3504.77	C-MT.77	35-210

- Trays for microtiter plates

Order number	Description	Number of MTP
SM3502A	E-tray (420 x 420 mm) for deepwell or microtiter plates	1-12
SM3501A	EX-tray (500 x 420 mm) for deepwell or microtiter plates	1-15
SM3503A	F-tray (800 x 420 mm) for deepwell or microtiter plates	1-24



Trays with sticky strips



Order number	Description	# of sticky strips
SMX330001	E-size tray	4 sticky strips
SMX340001	EX-size tray	5 sticky strips
SMX350001	F-size tray	8 sticky strips

Sticky strip: 385 x 85 x 3 mm

Trays with rubber mat



Order number	Description	
SM3602	Rubber mat EG	420 x 420 mm
SMX3602	Rubber mat EXG	500 x 420 mm
SM3603	Rubber mat FG	800 x 420 mm

Trays for centrifuge tubes (EPFL)



Order number	Description	# of holders
SMX3804	50 ml Falcon tubes EX-tray (EPFL)	3
SM3805	50 ml Falcon tubes F-tray (EPFL)	5

Order number	Description
SM3802C	SM3805 without holders and base plates
SMX3805A	Holder for 24 x 50 ml Falcon/TPP tubes mounted on a base plate for EPFL tray
SM3802B	4 microtiter plate holders (Duett) mounted on a base plate for EPFL tray

Trays with support bars



Order number	Description	# of longitudinal girders
SM4120.4	EA-tray with rubber mat and 4 cross supports	2
SMX4120.4	EXA-tray with rubber mat and 4 cross supports	2
SM4130.6	FA-tray with rubber mat and 6 cross supports	2

Floor stands



For a comfortable working height Kuhner offers floor stands for both the ISF1-X and LT-X incubator shakers. These are available in a choice of 400 mm or 765 mm high.

Order number	Description
SM1560	400 mm high for 2 x ISF1-X
SM1561	765 mm high for 1 x ISF1-X
SMX1760	400 mm high for 2 x LT-X
SMX1761	765 mm high for 1 x LT-X

Water baths



To reduce evaporation from shake flasks or microtiter plates a stainless steel water bath can be placed inside the incubator. This water bath is not fitted with an automatic water supply and must be topped up manually.

Order number	Description
SMX1533	ISF1-X
SMX1733	LT-X

Add-ons




BPM-60

Online measurement of dissolved oxygen and pH

BPM-60 (Bioprocess Monitoring) is a non-invasive, online measurement of dissolved oxygen and pH in shaken flasks.

- A socket integrated in the shaking table makes simple data communication and power supply possible without the risk of wiring breaking. With this technology no battery is required.
- DO and/or pH can be monitored simultaneously in four/eight different flasks
- Continuous recording with Kuhner Insight software
- Made for PAT (initiative of the FDA)
- Optimised cultivation conditions



FlowCon 2/3/4

Gas mixing device

The FlowCon is used for stabilizing the pH in cell cultivations with CO₂ or reducing oxygen concentration for microaerophilic organisms.

- Mixing up to four gases (gas mixtures can also be connected)
- Selectable flow rates: 0–1 [sL/min], 0–20 [sL/min], 0–200 [sL/min]

The FlowCon can be used as a stand-alone device or can be integrated with the Kuhner equipment family (Incubator shakers and OrbShakers).



FeedBeads®

Controlled glucose delivery by slow release technology

FeedBeads provide substrate limited fed-batch conditions in shake flasks or microtiter plates without the need for enzymes or additional equipment such as tubing or pumps.

- Easy handling
- Polymer based slow release system
- Suitable for high throughput screening (HTS)
- Improves screening security
- Reproducible pre-culture
- Synchronisation of pre-cultures
- Reduces overflow mechanism of the culture

For more information and further add-ons please visit:
www.kuhner.com



Kuhner

Adolf Kühner AG • since 1949

Headquarters

Dinkelbergstrasse 1
CH – 4127 Birsfelden (Basel)
Switzerland

phone +41 (0) 61 319 93 93
fax +41 (0) 61 319 93 94
office@kuhner.com

Kuhner Shaker Inc.

120 Glenn Way, Unit 1
San Carlos, CA 94070
USA

phone +1 650 595 19 97
fax +1 650 595 14 48

usoffice@kuhner.com

Kuhner Shaker S.A.

Mas Boada s/n
17462 Sant Marti Vell
Spain

phone +34 61 9394.735

esoffice@kuhner.com

Kuhner Shaker Ltd.

25 Croft Manor
Glossop
Derbyshire SK13 8PP
United Kingdom

phone +44 (0) 1457 864 287
fax +44 (0) 1457 863 398

ukoffice@kuhner.com

Represented by

For a distributor near you,
please visit:

www.kuhner.com